



DS系列
袋口缝合机



DS-2(II)



DS-2W



DS-C



DS-6



DS-6WAC



DS-7A/DS-7C



DS-9A/DS-9C



DS-9AW/DS-9CW

规格表

规格	型号	DS-2(II)	DS-2W	DS-C	DS-6	DS-6AC	DS-6HS	DS-6HSAC	DS-6W	DS-7A	DS-7C	DS-9A	DS-9AW	DS-9C	DS-9CW
最大转速(r.p.m.)		1,400	1,400	1,400	1,400	1,400	2,000	2,000	2,000	1,600	1,600	2,700	2,500	2,700	2,500
手动上袋		•	•	•	•	•	•	•	•			•	•	•	•
KS 系列缝口封口机										•	•				
自动上袋装置					•	•	•	•	•	•	•			•	•
最大袋口厚度(mm)		10	6	10	10	10	8	8	6	3	3	8	8	8	8
针杆行程(mm)		62	62	62	62	62	56	56	56	44	44	48	48	48	48
单机针		•		•	•	•	•	•		•	•	•		•	
双机针			•						•				•		•
线迹宽度(mm)		7~12	7~12	7~12	7~10.5	7~10.5	7~10.5	7~10.5	7~10.5	8	8	7~11.5	7~11.5	7~10.5	7~10.5
标准设定(mm)		10	10	10	10	10	10	10	10	8	8	10	10	10	10
双缝线链式线迹		•	•	•	•	•	•	•	•	•	•	•	•	•	•
单缝线链式线迹(注1)		•										•		•	
仅用于平缝		•	•						•	•		•	•		
仅用于胶带粘接缝合				•											
平缝/胶带粘接缝合(注2)					•	•	•	•			•			•	•
机动缝线切刀		•	•							•		•	•		
机动胶带切刀				•											
电磁控制的缝线/胶带切刀(注3)					•		•		•						
气动缝线/胶带切刀						•		•			•			•	•
气压(kg/cm ²)						4		4			4			4	4
耗气量(Nl/min)						2		3			2			3.5	3.5
手动注油及注油器		•	•	•	•	•	•	•	•	•	•				
自动油浴系统												•	•	•	•
标准皮带轮直径(mm)		112	112	112	100	100	100	100	100	101.6	101.6	100	100	100	100
变速皮带轮(注4)												•	•	•	•
三角皮带型式(注5)		M	M	M	M	M	M	M	M	A	A	M	M	M	M
机针型号		DRX2	DR-H30	DRX2	DRX2	DRX2	DRX2	DRX2	DRX2	DN-H29	DN-H29	DR-H30	DR-H30	DR-H30	DR-H30
标准机针型号		#25	#26	#25	#25	#25	#25	#25	#25	#26	#26	#26	#26	#26	#26
可替代机针型号		#26		#26	#26	#26	#26	#26	#26	#25	#25				
合成纤维线或棉线		20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9	20/6,20/9
0.75kw,4P,3PH(注6)							•	•	•			•	•	•	•
0.4kw,4P,3PH(注6)		•	•	•	•	•				•	•				

注:

(1) 单缝线部件不属于标准配置件。

(2) 除DS-C外, 皱纹胶带送纸器不属于标准配置件。

(3) 电磁铁驱动的切刀驱动器不属于标准配置件。

(4) 传动比为1:1.35。

(5) 三角皮带不属于标准配置件。

(6) 电动机不属于标准配置件。